

## Accessories and spare parts

 <p><b>4320290</b> Basic wall support</p>	 <p><b>4320301</b> 10g tested wall bracket</p> <p><b>4320300</b> 10g tested wall bracket including 12 V power supply (only for <b>V7 plus b emergency</b>)</p>
 <p><b>4320021</b> Mobile trolley</p> <p><b>3383007</b> Probe cleaner (polycarbonate)</p>	 <p>suction jar</p> <p><b>4383001</b> PC1 (polycarbonate, 1 L)</p> <p><b>4383000</b> PSU1 (polysulfone, 1 L)</p> <p>Disposable suction bags available, please consult</p>  <p>suction jar</p> <p><b>4383002</b> PC2 (polycarbonate, 1.75 L)</p> <p><b>4383012</b> PSU2 (polysulfone, 1.75 L)</p> <p>Disposable suction bags available, please consult</p>
 <p><b>4320032</b> Cable 12 / 24 V for ambulance</p>	 <p><b>4320033</b> Battery charger 220-12 V</p>
 <p><b>3320223</b> Transport bag</p>	 <p><b>0320014</b> Transport cover suitable for use with 10g wall bracket</p>
 <p><b>4340001</b> Metallic straight catheter</p> <p><b>4340002</b> Metallic curved catheter</p> <p><b>4340000</b> Metallic catheter handle</p>	 <p><b>0340015</b> Obstetric vacuum cups 50 mm</p> <p><b>0340016</b> Obstetric vacuum cups 60 mm</p> <p><b>0340017</b> Obstetric vacuum cups 70 mm</p>
 <p><b>0940023</b> PVC tube 8 x 13 mm (per meter, roll up to 30 m)</p>	 <p><b>3320534</b> Hydrophobic bacteria filter</p>
 <p><b>0310017</b> Disposable Yankauer cannula + 2 m suction tube</p>	 <p>Canister holder compatible with main brands of disposable liners (please consult)</p>



## Portable Suction Units



Puerto de Navacerrada 3  
28935 Móstoles, Madrid, SPAIN  
Tel.: +34 91 616 6000 • Fax: + 34 91 616 4892  
export@hersill.com  
[www.hersill.com](http://www.hersill.com)



ISO 10079-1:2015  
EN IEC 60601-1:2006  
EN IEC 60601-1-2:2007  
EN IEC 60601-1-6:2010  
EN 1789:2007+A1:2014

Leaflet no. IN-53202/18/02





	V7 ac	V7 dc	V7 plus ac	V7 plus dc	V7 plus b	V7 plus b emergency	V7 mx	V7g
With PC1 suction jar	5320201 5321201	5320211	5320241 5321241	5320251	5320261	5320281	5320236	5320271
With PC2 suction jar	5320202 5321200	5320212	5320242 5321240	5320252	5320262	5320282	5320237	5320273
Power supply	220 Vac 50Hz 110 Vac 60Hz	12V <sub>dc</sub>	220 Vac 50Hz 110 Vac 60Hz	12V <sub>dc</sub>	12V <sub>dc</sub> Battery	12V <sub>dc</sub> Battery	100/240 Vac 12V <sub>dc</sub> Battery	100/240 Vac 12V <sub>dc</sub> Battery
Free air suction flow	20 L/min	14 L/min	30 L/min	30 L/min	30 L/min	30 L/min	30 L/min	5 L/min Continuous/ Intermittent
Maximum vacuum	80 kPa 600 mmHg	75 kPa 562 mmHg	84 kPa 630 mmHg	84 kPa 630 mmHg	84 kPa 630 mmHg	84 kPa 630 mmHg	84 kPa 630 mmHg	20 kPa 150 mmHg
Electric power	250 W	18 W	120 W	85 W	85 W	85 W	160 W (ac) 84 W (dc)	35 W (ac) 30 W (dc)
Internal battery					12 V - 4,5 Ah Ac-Pb 65 min	12 V - 4,5 Ah Ac-Pb 65 min	12 V - 4,5 Ah Ac-Pb 65 min	12 V - 1,3 Ah Ac-Pb 120 min
AC Internal battery charger							✓	✓
AC/DC External battery charger					Optional	Optional		
10g tested wall bracket including 12 V power supply						✓		
Cable 12/24 V for ambulance		✓		✓	✓	✓	✓	✓
Bacteria filter	✓	✓	✓	✓	✓	✓	✓	✓
Noise level	49 ± 1,5 dB (AS) / 1 m							
Weight	3 Kg	2,2 Kg	3,5 Kg	2,5 Kg	4,2 Kg	4,2 Kg	4,5 Kg	2,5 Kg
Dimensions	Height		Width			Depth		
	250 mm		395 mm with PC1 jar 428 mm with PC2 jar			160 mm		
Space required to host in an ambulance, with 10g bracket	290 mm		395 mm with PC1 jar 428 mm with PC2 jar			168 mm		
Packing dimensions	460 x 210 x 290 mm (W x D x H)							



## High quality and high performance portable suction units.

Due to their versatility, they can be used in hospitals, ambulances, home-care therapies and other emergency services. Suitable for surgery, gynaecology and ORL.

High vacuum suction units: high flow (30 L/min), low flow (14 or 20 L/min) depending on the model.

Low vacuum suction unit: **V7g** Continuous-Intermittent (5 L/min). Specifically developed for gastric and wound drainage, and therapies requiring precise low vacuum conditions.

**V7 plus b, V7 plus b emergency and V7 mx** are specifically designed for ambulance, transport and emergency field use.

- **ABS ergonomical case.** Rear fixing system for wall bracket tested to resist accelerations and decelerations of 10g in longitudinal, transverse and vertical direction (according to European Norm UNE-EN-1789: 2000).
- **Piston type suction pump (V7g: membrane type suction pump).** All models oil-free and maintenance-free.
- **Vacuum control knob (V7g: intermittance programmer control knob and vacuum control knob).**
- **Vacuum gauge from / to:** 0-100 kPa / 0-760 mmHg. (V7g: vacuum display from/to: 0-20 kPa (0-150 mmHg)).
- **Water-proof ON/OFF switch with guard.**
- **Battery:** LED battery level indicator lights (included in all models).
- **PC1 /PC2 polycarbonate suction jar (1 L / 2 L) with overfilling safety valve:** Autoclavable up to 121 °C / 250 °F (Please check our accessory section for further configurations).
- **Bacteria filter and suction hoses included** (PVC tubes 8 x 13 mm). 2 m to patient hose.
- **Yankauer cannula.**
- **V7g: LED lights:** ON, intermittent, vacuum level, vacuum indicator and battery status. Intermittance programmer control knob and vacuum control knob.



V7 plus ac



V7 g



V7 plus ac  
with mobile trolley  
and probe cleaner



V7 plus b



V7 plus b emergency



V7 mx



10g tested wall bracket