2.1 2020



Gemological binocular stereozoom microscope, 7x...45x, tiltable stand, transmitted & incident light

Observation Method - Transmitted Light	Brightfield	Yes
	Darkfield	Yes
	Simple polarized light	As optional
Observation Method - Incident Light	Brightfield	Yes
	Darkfield	Yes
	Simple polarized light	As optional
Head	Туре	Binocular
	Construction material	Aluminum & Plastic molds / Aluminum gears
	Inclination	45°
	360° rotating	Yes
	Interpupillary distance (mm)	51-75
	Dioptric adjustment	On both tubes
	Head holder internal diameter (mm)	76
	Tube inner diameter (mm)	30
Eyepieces	Field number (mm)	21
_ <b>,</b> - <b>,</b> - <b>,</b>	Magnification	10x
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	23
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
	Retractable protections	Yes
Objective	Optical system	Greenough
	Anti-fungus treatment	Yes
	Zoom type	Achromatic
	Working distance (mm)	100
	Standard magnifications	7x-45x
	Zoom ratio	6.43
Focusing System	Туре	Coarse
	Coarse total travel (mm)	114
	Adjustable tension	Yes
	Head holder internal diameter (mm)	76
		. •
Stand	Туре	Fixed arm
	Tilting mechanism	Yes, full 90° tilt angle and 360° rotating
	Thung moonanism	1 00, run 00 tilt arrigie arra 000 Totatirig
Stage	Complexical clamp	Voc. adjustable
9-	Gemological clamp	Yes, adjustable

Transmitted	Туре	LED
Illumination	Darkfield illuminator	Yes, side-emitting LEDs
	Lever for dark background insertion	Yes
	Selector for illumination modes	Yes, 3 modes: - brightfield only - darkfield only
	1:14	- both brightfield and darkfield.
	Light source power (W)	2
	Illuminance (lux)	6,000
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	3
Incident Illumination	Turno	LED
Incident Illumination	Type	
	Light source power (W)	1
	Illuminance (lux)	20,000
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	3
Power Supply for	Туре	External
Illumination	Microscope connector	Jack, 2.1 mm
mammadon	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	12 Vdc 1.5 A
	Output voltage	12 Vuc 1.3 A
Accessories Included	Dust cover	Yes
	User Manual	Digital version (downloadable)
	- Training	2.3 (2011
Additional Information	Maximum sample height (mm):	90
<b>Product Dimensions</b>	Total height (mm)	480
	Head height (mm)	230
	Head width (mm)	140
	Head depth (mm)	150
	Base height (mm)	60
	Base width (mm)	210
	Base depth (mm)	270
Product Weight	(tea)	10
i roduct weight	(kg)	10