

Dräger Jaundice Meter JM-105 Jaundice Management

The Dräger Jaundice Meter JM-105 gives you consistent quality screening, cost-effectively delivered over the lifetime of the device. As a result you optimize the efficiency of your jaundice management program, which can help save time and money while delivering an exceptional standard of care.



Benefits

Effective Jaundice Screening

With the Jaundice Meter JM-105 you can accurately identify at-risk infants as young as 35 weeks gestational age. Effective screening can decrease readmission rates and durations of stay. Having dependable results in seconds rather than hours helps to increase patient safety and expedite decision making. New integrated flagging feature helps you keep track of patients in need of special attention and comply with your jaundice management protocols.

Easy to use, easy on everyone

The JM-105 expands the concept of ease of use. It also means an easier experience for all involved. When taking a TcB measurement with the JM-105 compared to an invasive TSB measurement, there's less stress on fragile newborns and their patients – which makes things easier on you. Screening with the JM-105 is fast and easy; simply clean the reusable tip with an alcohol wipe and take your measurement. No fumbling with disposable tips. And because the device connects to your hospital information system, transferring jaundice screening information to the infant's electronic medical record is effortless and accurate. Simply put, the Dräger Jaundice Meter JM-105 is gentle for the newborn and efficient for you.

Improved process and cost efficiency

The Jaundice Meter JM-105 streamlines jaundice screening practices by reducing time-consuming blood draws, scheduling of laboratory work, and processing costs. It improves efficiency by delivering reliable measurements with significantly fewer steps, which frees up more time for direct infant care. The data transfer functionality and barcode scanner help you optimise your screening program and reduce the risk of human error. Because the JM-105 has a reusable probe tip, it requires no disposables. With the volume of screenings performed in nurseries today, the cost of such disposable items can ultimately exceed the initial cost of the device itself. As a result, you save time and money while delivering an exceptional standard of care.

Related Products

D-12195-2016



BiliLux

The BiliLux is a compact and lightweight LED phototherapy light system for the treatment of neonatal unconjugated hyperbilirubinemia. It provides superior phototherapy performance, individualised therapy with electronic documentation capabilities and the flexibility for seamless integration into practically every workplace.

Technical Data

SPECIFICATIONS

DEVICE CLASSIFICATION

Protection class per IEC 60601-1 (Jaundice Meter)	Internally powered ME equipment, Type BF, continuous operation, not AP
Protection class per IEC 60601-1 (AC adapter)	Class I ME equipment, externally powered, Type BF, continuous operation, not AP
Ingress of liquids and particulate matter (IEC60601-1)	IPX0
Classification in accordance with EU Directive 93/42/EEC Appendix IX	Ila
UMDNS code/GMDN code	16-166/35475

ELECTRICAL SPECIFICATIONS

Battery	Internal NiMH
Number of measurements (when fully charged)	250
AC adapter	
Input	9 VDC, 500 mA
Output	100 V ~ to 240 V ~, 50/60 Hz, 11 VA to 18 VA
Light source	Pulse xenon arc lamp
Light source life	150,000 measurements
Sensors	Silicon photodiodes

PHYSICAL SPECIFICATION

Width	56 mm
Depth	45 mm
Height	168 mm
Weight	203 g ± 10 %

PERFORMANCE SPECIFICATIONS

Measurement range	0.0 mg/dL to 20.0 mg/dL (0 µmol/L to 340 µmol/L)
Clinical Data Standard Error of Estimate (SEE)	± 1.5 mg/dL or ± 25.5 µmol/L (> 35 weeks gestation) ± 1.6 mg/dL or ± 27.4 µmol/L (24 – 34 weeks gestation)

DATA TRANSMISSION

USB port	HL-7 or CSV
----------	-------------

AMBIENT CONDITIONS

DURING OPERATION

Temperature	10 °C to 40 °C (50 °F to 104 °F)
Atmospheric pressure	700 hPa to 1060 hPa (-400 m to 3000 m)
Relative humidity	30 % to 95 % (without condensation)

DURING STORAGE AND TRANSPORT

Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Relative humidity	5 % to 95 % (without condensation)
Atmospheric pressure	500 hPa to 1060 hPa

Notes

Notes

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

Manufacturer:

Draeger Medical Systems, Inc.
3135 Quarry Road
Telford, PA 18969-1042, USA

USA

Draeger, Inc.
3135 Quarry Road
Telford, PA 18969-1042, USA
Tel +1 800 4DRAGER
(+1 800 437 2437)
Fax +1 215 723 5935
info.usa@draeger.com

CANADA

Draeger Medical Canada Inc.
2425 Skymark Avenue, Unit 1
Mississauga, Ontario, L4W 4Y6
Tel +1 905 212 6600
Toll-free +1 866 343 2273
Fax +1 905 212 6601
Canada.support@draeger.com

Locate your Regional
Sales Representative at:
www.draeger.com/contact

