

LED COLD LIGHT SOURCE

FIBROLUX LED DUO

HIGH POWER LED LIGHT SOURCE

- LED Light Source
- 2 Independent Light Outputs
- Extensive LED lifespan: 60,000hours



The FIBROLUX LED DUO brings to you the latest technology in endoscopy light systems. Its exclusive design with 2 independent outputs allows you to use 2 equipment simultaneously.

LED COLD LIGHT SOURCE **FIBROLUX LED DUO**



Compatible with Storz and Olympus

- LED light source
- High intensity. 10,000 Klux (measured at the output of a standard fiber optic cable of 1.8 m x 4.8mm)
- 2 independent outputs
- Lights can operate alternate or simultaneously
- Extensive LED lifespan of 60,000 hours
- Light intensity can be regulated without color variation
- Low power consumption
- Double cooling system (fans with automatic speed control)
- Standby mode for minimum energy consumption (as per EuP Directive)
- Memory for light intensity setting
- Compatible with most fiber optic connections
- Robust unit with aluminum case
- Power supply of 100-240V, 50 – 60 Hz
- Dimesions (W, H, D): 320 x 155 x 286 mm
- Weight: 5 Kg



User-friendly control panel

OPTOMIC ESPAÑA S.A.

Madroño, 4. E-28770 Colmenar Viejo, Madrid, Spain
Tel: +34 91 804 44 44 • Fax: +34 91 803 84 14
export@optomic.com • www.optomic.com



Las especificaciones pueden sufrir cambios sin previo aviso

